

# KDS-LIRDCA-CA5XSL-2200

## 2MP 1080P Network Camera



### Features

- Day/ Nigh : color/ B& W (IR-CUT)
- Image Configuration : Saturation/ Brightness/ Contrast/ Sharpness, Mirror, 3D NR, White Balance, FLK (Flicker Control), Video Tampering
- Corridor Pattern
- Defog Mode
- ROI
- BLC
- WDR
- Motion Detection
- 3 Rectangular Zone Privacy Masking
- Recording Mode : NVR/ CMS/ Web
- 13 Languages
- Optional Audio
- Optional Support Max 128GB SD Card Slot
- RS 485
- Housing Metal, IP66
- Optional Wall Bracket
- IR Cut Filter
- Power Supply DC12V  $\pm$  10%, 950mA
- Operation Temperature : -20°C- + 60°C RH95% Max
- Storage Temperature : -20°C- + 60°C RH95% Max
- Dimension 119x98mm (  $\varnothing$  x H)
- Weight 800g

# KDS-LIRDCA-CA5XSL-2200

## Specification

<b>Model</b>	<b>KDS-LIRD-CA5XSL-2200</b>
Image Sensor	1/ 2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	2 MP 1080P
Effective Pixels	1945x1097 (H x V)
Compression	H.264/ H.264+/ H.265/ H.265+/ JPEG/ AVI/ MJPG
TV System	PAL/ NTSC
Electronic Shutter Time	Auto: PAL 1/ 25-1/ 10,000Sec; NTSC 1/ 25-1/ 10,000Sec
Minimun Illumination	0.01 Lux
S/ N Ratio	≥ 52dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Focus Length	2.7 - 13.5mm
Focus Control	Auto
Lens Type	Motorized
Pixels	3 MP
Night Vision Infrared LED	14μ x 24PCS
Infrared Distance	30M
IR Status	Auto Control
IR Power On	Auto Control
Ethernet	RJ-45 (10/ 100Base-T)
Protocol	TCP/ IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
Video Delay	0.3s (within the lan)
Main Stream 1	2048x1536 @ 15fps
Main Stream 2	1920x1080 @ 30fps
Main Stream 3	1280x720 @ 30fps
Sub Stream 1	720x480 @ 15fps / 720x480 @ 30fps
Tri Stream	352x288 @ 15fps / 720x480 @ 30fps
IE Brower	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari (lower than Ver12)
Smart Phone	iPhone, iPad, Android, Android Pad