

KDS-XVR33116HDB

Multi-Function XVR



Specification

Model	KDS-XVR33116HDB
System Processor	HI3531A
Operating System	Embedded LINUX
Video Input	Analog: 16*(TVI/ AHD: 5MP, AHD/ TVI/ CVI: 4MP, AHD/ TVI: 3MP, AHD/ TVI/ CVI: 1080/720P, Analog: 960H) Analog + Network: 14*Analog + 2* network(Max 8MP), 12*Analog + 4* network(Max 8MP), 10*Analog + *6 network(Max 8MP), 8*Analog + 8* network(Max 8MP), 6*Analog + 10* network(Max 8MP), 4*Analog + 12* network(Max 8MP), 2*Analog + 14*network(Max 8MP), Network: 32* network (Max 8MP) (Total incoming bandwidth ≤200M)
Video Input	16CH BNC
Signal Type	Analog/ AHD/ CVI/ TVI/ Network
Video Output	1HD, 1VGA, 1CVBS
Audio Input	2Channel, RCA
Two-way Audio	NO
Audio Output	1 Channel, RCA
Alarm Sensor Input	NO
Alarm Sensor Output	NO
Motion Detection	16 Channel (Max 32 Channel in pure network mode)
Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications(motion detection)
Email Alarm	Send Image to The Designated E-mail
PTZ Interface	RS485
PTZ Protocol	Pelco-D, Pelco-P
PTZ Baud Rate	110 - 921600
PTZ Address	0 - 255

KDS-XVR33116HDB

Display VGA	Resolution: 1920 x 1080P/ 60Hz, 1280 x 1024/ 60Hz
Display HD Output	Resolution: 3840 x 2160/ 30Hz, 1920 x 1080/ 60Hz, 1280 x 1024/ 60Hz
Display Split	36 Channel/ 25 Channel/ 16 Channel/ 9 Channel/ 8 Channel/ 4 Channel/ 1 Channel
Display Privacy Masking	3 Rectangular Zones (Each camera)
Display OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
Video Record Compression	H.264/ H.264+
Audio Record Compression	G711u
Recording Resolution	5MP (2592x1944), 5MP_HALF(1296x1944), 4MP (2560x1440), 4MP_HALF(1280x1440), 3MP (2048x1536), 1080P (1920x1080), 720P (1280x720), 960H (P:960x576/ N:960x480)
Video Quality	Worst/ Worse/ Ordinary/ Well/ Best
Record Rate	<p>Analog:</p> <p>PAL: 5MP(2592×1944 16*6fps),5MP_HALF(1296×1944 16*10fps), 4MP(2560×1440 16*8fps), 4MP_HALF(1280×1440 16*12fps),3MP(2048×1536 16*9fps),1080P(1920x1080 16*12fps), 720P(1280×720 16*25fps), 960H(960×576 16*25fps)</p> <p>NTSC: 5MP(2592×1944 16*6fps),5MP_HALF(1296×1944 16*10fps), 4MP(2560×1440 16*8fps), 4MP_HALF(1280×1440 16*15fps),3MP(2048×1536 16*9fps),1080P(1920x1080 16*15fps), 720P(1280×720 16*30fps), 960H(960×480 16*30fps)</p> <p>Pure IP:</p> <p>PAL: 4k@18×25fps,5MP@20×25fps,4MP@28×25fps,3MP@28×25fps,1080P@32×25fps, 960P@32×25fps,720P@32×25fps,D1@32×25fps</p> <p>NTSC: 4k@18×30fps,5MP@20×30fps,4MP@28×30fps,3MP@28×30fps,1080P@32×30fps, 960P@32×30fps, 720P@32×30fps, D1@32×30fps</p>
Decode Capability	4Channel 5M@30fps
Sync Playback	<p>Pure Analog: 16CH 5M@6fps,16CH 5MP_HALF@10fps, 16CH 4M@7fps, 16CH 4MP_HALF@12fps, 16CH 3M@9fps, 16CH 1080p@15fps</p> <p>Mix Mode: 2CH 5M@30fps, 2CH 4M@30fps, 3CH 3M@30fps, 4CH 1080P@30fps, 4CH 960P@30fps, 4CH 720P@30fps</p> <p>Pure IPC: 2CH 4K@30fps, 4CH 5M@30fps, 4CH 4M@30fps, 5CH 3M@30fps, 9CH 1080P@30fps, 9CH 960P@30fps, 9CH 720P@30fps</p>
Remote Playback	4 Channel/ 1 Channel
Search Mode	All, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast Play, Rewind, Digital Zoom, Full Screen
Smart Phone Playback	4 Channel
Backup Mode	USB Device(with format FAT 32)/ Network
Network Interface	1 RJ45 10M/ 100M/ 1000M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
CMS Software	Support Windows 7/ Windows 8/Windows 10
Extra Stream	CIF(1 - 25fps)
Smart Phone	iPhone, ipad, Android ,Android pad

KDS-XVR33116HDB

Hard Disk Driver interface	2 SATA Interface
Hard Disk Capacity	2 SATA Hard Disk (2.5"/ 3.5" SATA, Up to 12TB)
Language	22 Languages
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power Consumption	DC 12V ≤ 10W (Without Hard Disk)
Working Environment	-10°C - 55°C / 10°C - 90°C
Dimension	310x295x46mm (W x D x H)
Weight	3.5kg (without HDD)